

SIGN SIZE GUIDE

Viewing distance (m)	Min symbol-field height H (mm) — Z=80 (difficult conditions / fast traffic)	Suggested panel height (mm) — Z=80 (difficult conditions / fast traffic)	Min symbol-field height H (mm) — Z=100 (ambient/external light - baseline)	Suggested panel height (mm) — Z=100 (ambient/external light - baseline)	Min symbol-field height H (mm) — Z=120 (good contrast / short glances)	Suggested panel height (mm) — Z=120 (good contrast / short glances)	Min symbol-field height H (mm) — Z=200 (internally illuminated escape signs)	Suggested panel height (mm) — Z=200 (internally illuminated escape signs)
3	37.5	150	30	150	25	150	15	150
5	62.5	150	50	150	41.7	150	25	150
7.5	93.8	150	75	150	62.5	150	37.5	150
10	125	150	100	150	83.3	150	50	150
12	150	150	120	150	100	150	60	150
15	187.5	200	150	150	125	150	75	150
20	250	300	200	200	166.7	200	100	150
25	312.5	400	250	300	208.3	300	125	150
30	375	400	300	300	250	300	150	150
40	500	600	400	400	333.3	400	200	200
50	625	Custom (>600)	500	600	416.7	600	250	300
60	750	Custom (>600)	600	600	500	600	300	300